

<i>Name of the document</i> Declaration of performance Interior panel of pine, Hardwax treated	<i>Document nr</i> CPR1099	<i>Page</i> 1 of 3
<i>Prepared by</i> Michaela Pfeiffer	<i>Number of edition</i> 2	
<i>Approved by</i> Lars-Kristen Holst	<i>Replaces edition</i> 1	<i>Date</i> 2022-05-06

DECLARATION OF PERFORMANCE CPR1099

1. Productgroup and identification

Interior panel of pine ≥ 13 mm, hard wax oiled in all colours.

2. Product information

Sawn, planed or profiled wooden panels with or without pine battens. The panel is hard-waxed white, has a thickness of ≥ 13 mm and fire class D-s2,d0.

For additional or more detailed information about delivered product, in addition to what is stated below, see package specification or any attached commercial document.

3. The intended use of the product

Panel intended for walls, interior use.

4. Manufacturer

Company: [Moelven Wood AB](#)
Address: [Box 8006, Karlstad, Sweden](#)
Telephone: [+46 10 122 50 50](#)
E-mail: order.woodab@moelven.se
Webbsite: www.moelven.com

5. System for assessment and continuous of the construction product's performance

System 3 in AVCP.

6. Certification and stated performance

The product is produced according to the harmonized standard EN 14915.

The notified body MEKA (identification number 2040) has carried out fire tests to check fire growth rate, flammability, and smoke growth. MEKA has issued a classification report in accordance with EN 13501-1.

<i>Name of the document</i> Declaration of performance Interior panel of pine, Hardwax treated	<i>Document nr</i> CPR1099	<i>Page</i> 2 of 3
<i>Prepared by</i> Michaela Pfeiffer	<i>Number of edition</i> 2	
<i>Approved by</i> Lars-Kristen Holst	<i>Replaces edition</i> 1	<i>Date</i> 2022-05-06

7. Declared performance

Essential characteristics	Declared values		
Reaction to fire	Fireclass		
	Euroclass	D-s2,d0 according to EN 13501-1	
	Substrate		
	Mounting	Minimum density [kg/m³]	Fireclass EN 13501-1
	Mounted with or without airgap	525	A1/A2-s1, d0
	Without airgap	525	A1/A2-s1, d0
Thermal conductivity	25,2 (according to EN 14915)		
Application	I (indoors, according to CEN TS 15912)		
Intended area of use	W (walls)		
Durability	4 (according to EN 350-2)		
Density	480 kg/m ³ (minimum density)		
Sound absorption	0,10/0,30 (according to EN 14915)		
Water vapor permeability	20 (wet)/50 (dry) (according to EN 14915)		
Release of formaldehyde	E1		
Content of pentachlorophenol	NPD (no performance detected)		
Hazardous substances	NPD (no performance detected)		
Resistant to fixing	NPD (no performance detected)		

<i>Name of the document</i> Declaration of performance Interior panel of pine, Hardwax treated	<i>Document nr</i> CPR1099	<i>Page</i> 3 of 3
<i>Prepared by</i> Michaela Pfeiffer	<i>Number of edition</i> 2	
<i>Approved by</i> Lars-Kristen Holst	<i>Replaces edition</i> 1	<i>Date</i> 2022-05-06

8. Related technical documentation

The property of the product declared in section no.1 and 2 is in accordance with that property stated in section no.7. This declaration of performance is drawn up under the responsibility of the manufacturer listed in Section No. 4

Karlstad 2022-05-06

Lars-Kristen Holst, manager product management



.....
(signature)